

AQUASWEEP

		1/3 HP 115V	1/3 HP 230V	1/2 HP 115V	1/2 HP 230V	3/4 HP 115V	3/4 HP 230V	1 HP 115V	1 HP 230V
SPECIFICATIONS	KWs	.25	.25	.37	.37	.55	.55	.75	.75
	AMPS	8	4	10	5	10.7	6.8	11.5	8.2
	RPM	3450	3450	3450	3450	3450	3450	3450	3450
	GALLONS/MIN	300	300	400	400	450	450	500	500
	FLOW DISTANCE	40'	40'	50'	50'	60'	60'	75'	75'
	OSCILLATOR DIA	80'	80'	100'	100'	120'	120'	150'	150'

MAXIMUM CABLE LENGTH IN FEET FROM MOTOR TO MAIN POWER

		1/3 HP 115V	1/3 HP 230V	1/2 HP 115V	1/2 HP 230V	3/4 HP 115V	3/4 HP 230V	1 HP 115V	1 HP 230V
CABLE SIZE	12 AWG	175'	700'	160'	650'	125'	480'	75'	400'
	10 AWG	275'	1120'	250'	1020'	150'	760'	100'	630'
	8 AWG	430'	1720'	390'	1610'	200'	1200'	150'	990'
	6 AWG	680'	2680'	620'	2510'	350'	1870'	300'	1540'
	4 AWG	1050'	4180'	960'	3880'	700'	2890'	650'	2380'
	2 AWG	1600'	6320'	1460'	5880'	1100'	4370'	1050'	3610'
CABLE SUPPLIED		50' 12 GA	50' 12 GA	50' 12 GA	50' 12 GA	50' 10 GA	50' 12 GA	50' 10 GA	50' 12 GA

DO NOT USE AN EXTENSION CORD TO SUPPLY POWER TO THE MOTOR



13245 Barry Street, Holland, MI 49424
 scottaerator.com information@scottaerator.com
 800-WATER-45 (800-928-3745) (616) 392-8882

